






符合RoHS指令要求
CONFORM TO RoHS INSTRUCTIONS



电器特性参数/ELECTRICAL PARAMETER

步 进 角	STEP ANGEL	1.8° ±5%
相 数	PHASES	2
额定电压	RATED VOLTAGE	2.7 V
额定电流	RATED CURRENT	1 A
电 阻	RESISTANCE	2.7ohm±10% AT 20° C
电 感	INDUCTANCE	mH±20% AT 1k Hz, 1V RMS
保持力矩	HOLDING TORQUE	0.14N·m
运行力矩 (---PPS)		--- MIN.
	RUNING TORQUR(AT ---PPS)	(24VDC, RATED CURRENT, FULL STEP)
绝缘耐压	DIELECTRIC STRENGTH	500V AC 1 MINUTIE
绝缘电阻	INSULATION RESISTANCE	100 MΩ MIN
绝缘等级	INSULATION CLASS	B
温度上升	TEMPERATURE RISE	80K MAX. (SEE NOTE 2)
转子惯量	ROTOR INERTIA	14g·cm ² (0.12oz·in ²)
重 量	WEIGHT	APPROX. 180g (6.43 OZ)
允许轴向负载	ALLOWABLE THRUST LOAD	15N
允许径向负载	ALLOWABLE RADIAL LOAD	75N(ON THE SHAFT END)



CONFIRMED&ACCEPTED BY CUTORER (客户确认&接受)						物料号			
CUSTOMER'S COMPANY CHOP&SGNATURE 盖章&签名									
一般公差 TOLERANCE ±0.3/±3°		版本 REV.	年 月 日 DATE	变更番号 ECO NO.	变 更 内 容 REVISIONS	设计 BY	备 注 NOTE	REV.	A
制 图/DRAWN		比例 SCALE	1:1	品 名 TITLE	35H234-1004AG5.18			三视图 THIRD ANGLE PROJECTION 	
设 计/DESIGNED									单位 UNIT
审 核/CHECKED									
承 认/APPROVED		上海四横申机制造有限公司						页 SHEET	1/1