






符合RoHS指令要求
CONFORM TO RoHS INSTRUCTIONS



电器特性参数/ELECTRICAL PARAMETER

步 进 角 STEP ANGEL	1.8° ±5%
相 数 PHASES	2
额定电压 RATED VOLTAGE	10 V
额定电流 RATED CURRENT	0.5 A
电 阻 RESISTANCE	21 ohm±10% AT 20° C
电 感 INDUCTANCE	22 mH±20% AT 1k Hz, 1V RMS
保持力矩 HOLDING TORQUE	0.10 N·m
运行力矩 (—PPS)	— MIN.
RUNING TORQUR (AT —PPS)	(24VDC, RATED CURRENT, FULL STEP)
绝缘耐压 DIELECTRIC STRENGTH	500V AC 1 MINUTIE
绝缘电阻 INSULATION RESISTANCE	100 MΩ MIN
绝缘等级 INSULATION CLASS	B
温度上升 TEMPERATURE RISE	80K MAX. (SEE NOTE 2)
转子惯量 ROTOR INERTIA	10 g·cm ²
重 量 WEIGHT	APPROX. 140g
允许轴向负载 ALLOWABLE THRUST LOAD	15N
允许径向负载 ALLOWABLE RADIAL LOAD	75N(ON THE SHAFT END)



CONFIRMED&ACCEPTED BY CUTORER (客户确认&接受)							品 名 步进电机规格书
CUSTOMER'S COMPANY CHOP&SIGNATURE 盖章&签名							
一般公差 TOLERANCE ±0.3/±3°		版本 REV.	年 月 日 DATE	变更番号 ECO NO.	变 更 内 容 REVISIONS	设计 BY	
制 图/DRAWN		比例 SCALE 单位 UNIT		1:1	物料号	备 注 NOTE REV. A	
设 计/DESIGNED							
审 核/CHECKED				mm	型 号		
承 认/APPROVED				35H228-0504AG71.2			
						页 SHEET	1/1